



ALUMINUM BODY SIDE ROLL AND FRONTAL IMPACT PROTECTION MAXIMUM O.A.H. - 122.00"

NOTE
 DIMENSIONS SHOWN ARE APPROXIMATE AND ARE SUBJECT TO MINOR DEVIATIONS AS MAY OCCUR OR BE NECESSARY IN CONSTRUCTION. MINOR DETAILS NOT SHOWN.

1. ONSPOT AUTOMATIC TIRE CHAINS TO BE PROVIDED AT THE REAR
2. AIR INLET WITH DISCONNECT COUPLING IN THE DRIVER SIDE STEPWELL
3. (2) ZIMMATIC SAC-44-E WHEEL CHOCKS SHIPPED LOOSE
4. BATTERY CHARGER INDICATOR LOCATED IN THE CAB PER SHOP ORDER
5. BATTERY CHARGER LOCATED IN THE BODY PER SHOP ORDER
6. ONE 120V 5-PLACE RECEPTACLE STRIP LOCATED PER SHOP ORDER
7. ONE LAZY SUSAN TOOL MOUNTING TURNABLE LOCATED PER SHOP ORDER
8. ONE HANNAY MODEL ECR 1618-17-18 CABLE REEL FOR 200' OF 10/3 CORD LOCATED IN B1

REV	DATE	BY	CH	ENFORCER
06MAR24	LST	JLL		
01FEB24	LST	JLL		
17NOV23	LST	PHA		

Pierce MANUFACTURING INC.

JOB NO. 39127
 SCALE 1:24
 DATE
 DRAWN BY LST
 08NOV23
 CHECKED BY PHA
 10NOV23
 SHEET SIZE D
 SHEET NO. 1 OF 1